



TURBO RELEASE

PREMIUM FORM RELEASE AGENT

Product Description

OCM Turbo Release is a premium, non-staining, chemically active, highly refined mineral oil based form release coating. Formulated to provide the concrete construction forming industry with an environmentally compliant release agent for both indoor and outdoor application. OCM Turbo Release is formulated without diesel fuel; forms are ready for re-use almost instantly. OCM Turbo Release produces a smooth, void free, architectural concrete surface. VOC compliant.

General Uses

OCM Turbo Release will aid in the release of the form from hardened concrete on the widest range of forming material. OCM Turbo Release will help eliminate the general "petroleum odor" from the commercial jobsite. Ideal for both interior and exterior concrete forming applications.

Features

- Ensures easy stripping of forms.
- Produces smooth natural architectural surfaces - chemical action is not harmful to the concrete surface.
- Will not retard, etch, or soften concrete surfaces, even if over-applied.
- Run-down is reduced and reinforcing steel stays cleaner.
- May be used on concrete structures that will store potable water.
- Has a positive release that keeps forms clean - no cleaning between pours is necessary.
- Repeated use makes wood forms water-repellent and extends their useful life.
- Inhibits rust formation on steel forms.
- Easy to apply
- No deleterious effect upon the natural bonding characteristics of secondary toppings or coatings, caulks, or sealants.
- Reduces bug holes and extends the life of most forming materials.

Standards

Meets the requirements of Corps of Engineers specifications CW 03101, section 2.1.2. VOC Compliant and Conforms to the Ozone Transportation Commission (OTC) guidelines for VOC regulations.

Instructions For Use

OCM Turbo Release should be applied in a thin uniform film with a sprayer, brush or roller. No special application equipment is necessary, but a spray application is the most practical. Ponding or puddling is to be avoided

Specific applications are as follows:

Aluminum, High Density Plywood, Plastic or Steel
2,500 sq. ft./U.S. gallon

Medium Density Plywood
2,000 sq. ft./U.S. gallon

BB Grade Plyform
1,500 sq. ft./U.S. gallon

Plywood & Other Dimensional Lumber
1,200 sq. ft./U.S. gallon

Packaging

- 275 gallon (1040.9 L) totes
- 55 gallon (208 L) drums
- 5 gallon (18.9 L) pails

Limitations/Warning

- Refer to Safety Data Sheet before use.
- Do not over apply.
- Do not use as a bond breaker for tilt-up construction.
- Do not use on Styrofoam or latex molds.
- Do not use on plaster molds unless coated with a suitable sealer.
- Colder temperatures will increase the viscosity of OCM Turbo Release.

Contains petroleum distillates. Do not take internally. Do not breathe vapors. Avoid prolonged contact with skin. If swallowed, call physician. If splashed in eyes, wash repeatedly with clean water and call physician. Keep away from heat, sparks and open flame.

VOC content: less than 250 g/L. Complies with USA and Federal AIM VOC standards. Do not thin or dilute.

Technical Services

OCM Inc. Technical Service Department provides complete product and technical support.

Limited Warranty: Subject to the conditions and limitations stated below, OCM Inc. warrants this product to be free from manufacturing defects for a period of one (1) year from the date of purchase of the product. As conditions of this limited warranty, you may be required. At the option of OCM Inc. to provide proof of product purchase and use. DISCLAIMER: THIS LIMITED WARRANTY IS GIVEN IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES BASED ON SAMPLES OR ORAL STATEMENTS, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. EXCLUSIVE REMEDY: The sale and exclusive remedy for a breach of this limited warranty is replacement of the OCM Inc. product that is proven defective. In the event this sole and exclusive remedy fails of its essential purpose, the liability of OCM Inc. is limited to return of the original purchase price. EXCLUSION: OCM Inc. is not responsible for workmanship not in accordance with OCM Inc. instructions and industry standard guidelines. OCM Inc. IS NOT LIABLE FOR ANY INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES, INCLUDING LOSSES DUE TO DELAYS, INCURRED BY THE PURCHASER OR ANY OTHER PARTY.

OCM Inc. 1215 Henri Dr, Wauconda, IL 60084 Tel 866 457 5710 Fax 847 462 4258

www.ocm-inc.com