


WELDED WIRE GIRDER



The need for more energy efficient construction has guided the precast concrete industry into designing more cost effective and energy efficient precast wall panels that can be produced more efficiently. Recent federal and state regulations have driven the industry to develop better and more efficient precast "sandwich panels" which utilize a middle layer of insulation sandwiched by two layers of concrete.

OCM now offers Welded Wire Girder to meet the needs of "sandwich panel" construction. It is designed to properly transfer and distribute the loading to the different wythes of the sandwich panel, therefore eliminating the need for any solid sections between the wythes and eliminating thermal bridging. OCM Welded Wire girder connects the wythes through the insulation, and it has the resiliency to expand and contract with the independent thermal induced movements of the outer wythe. Welded Wire Girder will help prevent the issues of high stress points, thermal areas, cold spots, and wet areas on the interior wythes.



*WIRE IS PRODUCED ACCORDING TO ASTM A82

TOP WIRE

Maximum Size - 0 Gauge (.306" diameter)
Minimum Size - 4 Gauge (.225" diameter)

BOTTOM WIRE

Maximum Size - 0 Gauge (.306" diameter)
Minimum Size - 4 Gauge (.225" diameter)

DIAGONAL WIRE

Maximum Size - 3 Gauge (.243" diameter)
Minimum Size - 6 Gauge (.192" diameter)

HEIGHT

Minimum size is 3" to 9" maximum in incremental change in height of 1/2".

LENGTH

Standard Lengths are 10' and 12'.
Available with Mill Galvanized Wire.

INSTALLATION

1. Install bottom wythe mesh and place single girder into form, then tie it to the mesh or prestressed cables
2. Pour bottom wythe of concrete, raise or rotate single girder to a vertical position such that 2/3 of the girder height is standing out of the concrete.
3. Install insulation board in strips between the girder and walk along the insulation board, pressing the insulation board in and around the girder diagonal wires.
4. If any gaps or spaces occur, tape or caulk gaps to prevent any concrete or thermal bridging between the top and bottom wythes.
5. Install top wythe mesh and tie to girder or to prestressed cables for support and proper positioning in center of top wythe. Then place remaining concrete.

OCM, Inc.

1215 Henri Drive, Wauconda, IL 60084

Telephone: 866-457-5710 Fax: 847-462-4259

www.ocm-inc.com

Stocking Locations:

| | | | | |
|--|---|--|---|--|
| Denver 4120 York St. Denver, CO 80216 | Atlanta 605 Wesleyan Drive SW Atlanta, GA 30336 | Dallas 11625 Columbia Center Dallas, TX 75229 | Houston 5615 Armour Drive Houston, TX 77020 | Portland 1525 SE 10 th Ave. Portland, OR 97214 |
| Northern California 814 Striker Ave. Suite B Sacramento, CA 95834 | Southern California 2342 E. Valencia Dr. Fullerton, CA 92831 | New Orleans 1125 Barataria Houma, LA 70360 | New Jersey 192 Clifford St. Newark, NJ 07105 | Ft. Lauderdale 200 S.W. 12th Avenue Pompano Beach, FL 33069 |