



Aluminum Form Tie

Description:

Aluminum form ties secure aluminum forms in order to pour the desired wall thickness. These ties are used predominantly for poured wall basement foundations around the country.

Features:

- Available in both Full & Nominal sizes.
- Combo ties available as make-to-order.
- Designed for easy break off.
- 3,600 safe work load with a 2:1 safety factor.
- Made from high strength steel to ensure consistent quality.
- Ties are tested for quality control in our Chicago facility.
- Ties are compatible with all major aluminum forming systems in the industry.

Additional Notes: Additional lengths available upon request. Water seal available upon request. SWL provides a safety factor of approximately 2 to 1.

Item Number	Safe Working Load (lbs)	Filler Type	End	Wall Thickness Size (in)
AFT0810NRETQN	3,600	Nominal	Round	8"-10" (Combo)
AFT24NRETQN	3,600	Nominal	Round	24"
AFT22NRETQN	3,600	Nominal	Round	22"
AFT20NRETQN	3,600	Nominal	Round	20"
AFT18NRETQN	3,600	Nominal	Round	18"
AFT16NRETQN	3,600	Nominal	Round	16"
AFT14NRETQN	3,600	Nominal	Round	14"
AFT06NRETQN	3,600	Nominal	Round	6"
AFT12NRETQN	3,600	Nominal	Round	12"
AFT10NRETQN	3,600	Nominal	Round	10"
AFT09NRETQN	3,600	Nominal	Round	9"
AFT08NRETQN	3,600	Nominal	Round	8"
AFT06FRETQN	3,600	Full	Round	6"
AFT24FRETQN	3,600	Full	Round	24"
AFT22FRETQN	3,600	Full	Round	22"

Item Number	Safe Working Load (lbs)	Filler Type	End	Wall Thickness Size (in)
AFT20FRETQN	3,600	Full	Round	20"
AFT18FRETQN	3,600	Full	Round	18"
AFT16FRETQN	3,600	Full	Round	16"
AFT14FRETQN	3,600	Full	Round	14"
AFT12FRETQN	3,600	Full	Round	12"
AFT10FRETQN	3,600	Full	Round	10"
AFT09FRETQN	3,600	Full	Round	9"
AFT08FRETQN	3,600	Full	Round	8"