



2 Strut Conefast Coil Tie 3/4"

Description:

OCM Conefast Coil Ties are one of the most economical and versatile form tie systems available. They are commonly used with self cleaning Coil Rod or Coil Bolts. The Conefast coil Ties have extended coils that protrude beyond the end of the struts allowing for a Conefast (Screw On) Cone to be attached.

Features:

- When used with cones they will provide a setback of metal to reduce corrosion staining on finished wall
- Can be provided as plain or mechanically galvanized
- When used with cones can be used as combination tie and form spreader
- Used for architectural walls, and can also be used without cones

Additional Notes: Additional lengths available upon request. Water seal available upon request. SWL provides a safety factor of approximately 2 to 1.

Item Number	Safe Working Load (lbs)	Tie Length (in)	Wall Thickness (With 1" Setback) (in)	Weight Per Piece (lbs)	Box Quantity
CT7506SP	6,750 lbs.	6	8	0.75	100
CT7508SP	6,750 lbs.	8	10	0.75	100
CT7510SP	6,750 lbs.	10	12	0.9	100
CT7512SP	6,750 lbs.	12	14	0.98	100
CT7514SP	6,750 lbs.	14	16	0.98	100
CT7516SP	6,750 lbs.	16	18	1.14	100
CT7518SP	6,750 lbs.	18	20	1.14	100
CT7520SP	6,750 lbs.	20	22	1.32	100
CT7522SP	6,750 lbs.	22	24	1.39	100
CT7524SP	6,750 lbs.	24	26	1.48	100