



Slab Bolster Upper-Epoxy

Description:

OCM Slab Bolster Upper Epoxy Coated metal bar supports are used in commercial concrete projects to support upper and lower mats of reinforcing steel in elevated concrete decks, footings, slab on grade, slab on metal deck, bridge decks and other applications.

Features:

- Available in heights ranging from 3/4" to 6" in 1/4" increments.
- Manufactured in 60" Lengths.
- Epoxy Coating is done at approved coating suppliers within the United States with epoxy powder that is supplied by manufacturers that supply 100% Made in USA material. The epoxy powder meets the requirements of ASTM A775, AASHTOM254 and /or ASHTOM284 and is applied at a minimum thickness of 6 mils to satisfy the DOT requirements for all states.
- The Bar Supports supplied by OCM Inc. meet CRSI and "Buy America" requirements.

Additional Notes: Please inquire about domestic and CRSI requirements. Other sizes are available, please contact OCM.

Item Number	Weight Per Piece (lbs)	Height (in)	Bundle Quantity (lf)
SBU300-E	0.48	3"	100
SBU600-E	7.64	6"	100
SBU550-E	5.64	5-1/2"	100
SBU525-E	4.64	5-1/4"	100
SBU500-E	3.64	5"	100
SBU450-E	1.64	4-1/2"	100
SBU425-E	0.64	4-1/4"	100
SBU400-E	0.64	4"	100
SBU350-E	0.52	3-1/2"	100
SBU325-E	0.48	3-1/4"	100
SBU275-E	0.48	2-3/4"	100
SBU250-E	0.44	2-1/2"	100
SBU225-E	0.42	2-1/4"	100

Item Number	Weight Per Piece (lbs)	Height (in)	Bundle Quantity (lf)
SBU200-E	0.4	2"	100
SBU75-E	0.38	3/4"	100
SBU175-E	0.4	1-3/4"	100
SBU150-E	0.4	1-1/2"	100
SBU125-E	0.39	1-1/4"	100
SBU100-E	0.38	1"	100