

# Taper Tie- Euro Thread

Technical Product Data Sheet



## Description

Euro Taper Ties are used in forming situations where the ties are completely removed after the concrete has cured. Commonly used with European-style gangform systems, Euro Taper Ties enable contractors to efficiently assemble and strip formwork. Applying waterproof grease evenly on each Euro Taper Tie prior to concrete placement facilitates removal

## Features

- Available in 15mm or 20mm diameters.
- Manufactured in 20" to 48" lengths.
- Manufactured from High strength steel
- Varying Taper for wide array of form systems

| Product Code | Product Description      | Taper Dimension | S.W.L.     |
|--------------|--------------------------|-----------------|------------|
|              | 15mm Euro Taper Tie, 30" | 5/8" to 7/8"    | 18,750 lbs |
|              | 15mm Euro Taper Tie, 38" |                 |            |
|              | 15mm Euro Taper Tie, 42" |                 |            |
|              | 15mm Euro Taper Tie, 36" | 5/8" to 1"      | 18,750 lbs |
|              | 15mm Euro Taper Tie, 42" |                 |            |
|              | 15mm Euro Taper Tie, 48" |                 |            |
|              | 15mm Euro Taper Tie, 54" |                 |            |
|              | 15mm Euro Taper Tie, 60" |                 |            |
|              | 20mm Euro Taper Tie, 42" | 7/8" to 1"      | 32,500 lbs |
|              | 20mm Euro Taper Tie, 48" |                 |            |
|              | 20mm Euro Taper Tie, 54" |                 |            |
|              | 20mm Euro Taper Tie, 60" |                 |            |
|              | 20mm Euro Taper Tie, 42" | 7/8" to 1-1/4"  | 32,500 lbs |
|              | 20mm Euro Taper Tie, 48" |                 |            |
|              | 20mm Euro Taper Tie, 54" |                 |            |
|              | 20mm Euro Taper Tie, 60" |                 |            |

**Comments:** 2:1 safety factor

## OCM Limited Warranty

All recommendations, statements and technical data contained herein are based on tests we believe to be reliable and correct; however, accuracy and completeness of said tests are not guaranteed and are not provided as an express or implied warranty. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. In the event that a product supplied by OCM, Inc. proves to not meet the OCM, Inc. published dimensional or other specifications of the product, an OCM, Inc. representative will review such product and circumstances to determine whether a replacement is warranted. OCM, Inc.'s and its manufacturer's sole responsibility shall be to replace, at OCM, Inc.'s sole discretion that product or portion of the product which OCM, Inc. deems to be defective, within six months of the delivery of the product. OCM, Inc. disclaims all other warranties or conditions, whether express or implied, including an implied warranties of merchantability or fitness for any particular purpose. In no event shall OCM, Inc. or its parent or affiliated companies be liable for delay caused by defects, for loss of use, or for any indirect, incidental, special, or consequential damages or for any charges or expenses of any nature whatsoever. In no event shall OCM, Inc.'s liability exceed the purchase price paid for the particular affect OCM, Inc. products.

**OCM, Inc.**

**1120 E. Peterson Road, Grayslake, IL 60030**  
**Toll Free: 866-457-5710 • Phone: 847-462-4258 • FAX: 847-462-4259**  
**sales@ocm-inc.com**

Please do not place orders with this email address, it is for informational purposes only.